

CM360 Desktop Condenser Microphone



Features

This is a newly developed metal-based conference microphone with multiple national patents. This microphone not only has original appearance and innovative structure, but also with excellent electric-acoustic level higher than the national standard.

Description

- Condenser microphone for conference system
- With full anti-interference from electromagnetic/ mobile phone/ feedback
- Wide frequency, high-fidelity, ensure clear and charming voice
- Sensitivity: 30mV/Pa
- Frequency response: 30Hz -20kHz
- Output impedance: $\leq 75\Omega$
- Power supply: DC 3V (2xAA batteries) or phantom +48V
- Condenser MIC, stable with less noise.
- 45cm Gooseneck Microphone (Customized up to 60cm)
- Hyper-cardioid microphone, pickup distance 10-60cm

Specification

Regular type length	45cm
Elongated type length	60cm
Base dia	13cm (patent design)
Base weight	0.55kg
Base material	zinc base alloy
Plug	Appearance and structure patent
Powersupply	Condenser
Frequency Range	30-20kHz
Sensitivity	30 mV/Pa
Polar Pattern	Ultra-cardioid
Horizontal Polar	18dB differences from 0°to 135° (at 1 khz)
Output impedance	≤ 75Ω
Output	balanced output
The ideal sound pickup range	10-60cm
Power supply	2 kinds power, DC3V or 48V phantom power
Power Consumption	DC 3V 15mA Two AA1.5 V alkaline batteries can work for more than 250 hours
Accessories:	10m extension cord including 02 jack heads (Positive/negative) and anti-sound absorbing button

